SPEED TECHNOLOGY®
An ISO 9001 : 2015 Certified Company

Regd.Office : U-9, Kuber Complex, Dr. Yagnik Road,
Rajkot - 360 001 (INDIA)
PHONE : +91 98242 99869 / 89808 02072
E-MAIL : info@speedtechnology.in
Website : www.speedtechnology.in

Connecting your Business

HD331A



Hotel/hospitality features

DECT handset

Anti-bacterial housing

HD audio

Wireless flexibility for the hotel and guest sector

The Snom HD331A is an analogue, slim-designed hotel/guest room phone that offers users the greatest possible freedom of movement with its cordless DECT handset. GDPR-compliant by design, it offers the most important features of a hotel phone such as speed dial buttons, hands-free calling, hold and mute. If required, it can be expanded with up to 3 additional Snom HD3 type DECT handsets. The antibacterial housing protects against germs and is easy to clean. The large, optical LED call and message indicator as well as the individual labelling options complete the overall picture of an attractive room phone.

SPEED TECHNOLOGY®
An ISO 9001 : 2015 Certified Company

Regd.Office : U-9, Kuber Complex, Dr. Yagnik Road,
Rajkot - 360 001 (INDIA)
PHONE : +91 98242 99869 / 89808 02072
E-MAIL : info@speedtechnology.in
Website : www.speedtechnology.in

Technical specification

Basics and equipment

- Product information
  - Analog guest room phone | Cordless DECT handset | PN 00007033
  - Colour: gunmetal black and black
  - Anti-bacterial housing
- Equipment
  - Sturdy, solid construction
  - Customizable handset accent piece for color or branding opportunities
- Placement: indoor, desktop, nightstand

Dimensions and weight

- Dimensions (H × W × D, approx.)
  - Cordless DECT handseton the base cradle 216 mm × 82 mm × 110 mm
- Weight (approx.)
  - Cordless DECT handseton the base cradle: 500 g

Indicators and keys

- 7 LED indicators
  - Cordless DECT handset
    - Flash/Talk key indication: 1 red LED
    - Mute status indication: 1 red LED
    - Speakerphone mode:1 red LED
    - Hold status indication: 1 red LED
    - Low battery indication: 1 red LED
  - Telephone base
    - Call status indication | Message waiting indication (MWI): 1 red LED
    - Charging indication: 1 red LED
- 31 hard keys in total
  - Cordless DECT handset
    - 12 keys (standard ITU telephone keypad) backlit
    - 4 dedicated audio keys
      - Speakerphone(with red LED)
      - Mute (with red LED)
      - Volume + / - (rocker)
    - 3 programmable function keys: Speed dialling
    - 5 dedicated function keys
      - Offhook (with red LED)
      - Onhook/ Cancel
      - Hold (with red LED)
      - Message
  - Telephone base
    - 1 dedicated function key
      - Handset localisation

Interfaces and connections

- Power options
  - Telephone base
    - Power adapter: 6 V
  - Cordless DECT handset
    - Battery (CORUN)lithium-ion , 3.7 V, 1000 mAh, removable, rechargeable, up to 7 h talk time, up to 168 h standby time, up to 11 h charging time
- Wired interfaces
  - Power adapter: coaxial power connector (socket)
  - Network connectivity (PABX): RJ11-6P4C socket
- Wireless interfaces
  - Handsets: DECT

Technical specification

Audio devices and features

- Cordless DECT handset
  - Microphone
  - Handset earpiece
  - Hearing aid compatible (HAC)
- External speaker
  - Speakerphone mode

DECT technology and features

- Standard: DECT
  - Handsets: up to 4 total
  - Wideband audio
- Frequency band
  - EU & UK &AU: 1,881.792 - 1,897.344 MHz
- Easy registration to compatible base stations

Call features

- Quick call answer (by simple pick-up from the base/charger)
- Speed dialling via function keys
- Mute microphone (via dedicated function key)
- Speakerphone mode(via dedicated function key)
- Hold (via dedicated function key)

Interoperability

Environmental conditions

- Operating ambient temperature
  - 5 °C - +45 °C
- Humidity (non-condensing):
  - 5 % - 95 %

Package contents

- Hardware
  - Telephone base
  - Cordless DECT handset
  - Power adapter
  - Battery
- Documentation
  - Quick Installation Guide

Snom accessories and compatible devices

- DECT handset &charging cradle[1]
  - Up to 3 × HD3 (PN 00007011)
- Battery PN 00004627

Technical specification

Series overview



HD30L[1]



HD300[1]



HD331[1]



HD350W[1]



HD351W[1]



HD3

[1] Also available as analogue model