Connecting your Business

HD351A



Hotel/hospitality features

DECT handset

Customisable faceplate

Anti-bacterial housing

HD audio

Elegant analog guest phone with wireless DECT handset for the hotel/hospitality sector

The Snom HD351A is a well-designed analog cordless guest room telephone.
The antibacterial housing to protect against germs is a real plus in everyday life. A clearly visible LED alerts the guest to calls or waiting messages. Customisation is done via faceplates. Wall or table mounting is possible. The device is GDPR compliant by design: no data storage of personal information such as dialled phone numbers is carried out!

Technical specification

Basics and equipment

- Product information
  - Analog guest room phone | Cordless DECT handset | PN 00007031
  - Colour: gunmetal black
  - Anti-bacterial housing
- Equipment
  - Sturdy, solid construction
  - Telephone base: Fully customisable faceplate for hotel branding and dialing instructions [1]
  - Cordless DECT handset: Customisable section for colour or hotel branding [1]
- Placement: indoor, desktop, nightstand, wall mounting

Dimensions and weight

- Dimensions (H × W × D, approx.)
  - Cordless DECT handset (on the base cradle, desk mounted): 109 mm × 146 mm × 182 mm
  - Cordless DECT handset (on the base cradle, wall mounted): 109 mm × 56 mm × 216 mm
- Weight (approx.)
  - Cordless DECT handset (on the base cradle): 796 g

Keys

- 50 hard keys in total
- Telephone base
  - 12 keys (standard ITU telephone keypad)
  - 4 dedicated audio keys
    - Mute (with red LED)
    - Speakerphone (with red LED)
    - Volume +
    - Volume -
  - 3 dedicated function keys
    - Message
    - Hold
    - Emergency
  - 8 programmable function keys
    - Speed dialling
- Cordless DECT handset
  - 12 keys (standard ITU telephone keypad) backlit
  - 4 dedicated audio keys
    - Mute (with red LED)
    - Speakerphone (with red LED)
    - Volume +
    - Volume -
  - 3 programmable function keys
    - Speed dialling
  - 4 dedicated function keys
    - Talk (with green LED)
    - Off
    - Message
    - Hold

SPEED TECHNOLOGY®
An ISO 9001 : 2015 Certified Company

Regd.Office : U-9, Kuber Complex, Dr. Yagnik Road,
Rajkot - 360 001 (INDIA)
PHONE : +91 98242 99869 / 89808 02072
E-MAIL : info@speedtechnology.in
Website : www.speedtechnology.in

Technical specification

Indicators

- 9 LED indicators
- Telephone base
  - Call status indication | Message waiting indication (MWI): 1 red LED
  - Mute status indication: 1 red LED
  - Speakerphone mode:1 red LED
  - Charging indication: 1 red LED
- Cordless DECT handset
  - Message waiting indication (MWI): 1 red LED
  - Flash/Talk key indication: 1 green LED
  - Speakerphone mode:1 red LED
  - Mute status indication: 1 red LED
  - Low battery indication: 1 red LED

Interfaces and connections

- Power options
  - Telephone base
    - Power adapter
      - 100 - 240 V AC / 50 - 60 Hz / 500 mA | 5 V DC / 2 A
  - Cordless DECT handset
    - Battery lithium-ion , 3.7 V, 1,000 mAh, removable, rechargeable, up to 7 h talk time , up to 144 h standby time
- Wired interfaces
  - Network connectivity (PABX): RJ11-6P2C socket
  - Power adapter: coaxial power connector (socket)
- Wireless interfaces
  - Handset: DECT[3]

Audio devices and features

- Telephone base
  - Casing microphone
  - Casing speaker
- Cordless DECT handset
  - Microphone
  - Handset earpiece
  - Hearing aid compatible (HAC)

DECT technology and features

- Standard: DECT[3]
  - Handsets: up to 4 total
  - Wideband audio
- Frequency band
  - EU & UK:1,881.792 - 1,897.344 MHz
- Easy registration to compatible base stations

Call features

- Quick call answer (by simple pick-up from the base/charger)
- Speed dialling via function keys
- Mute microphone (via dedicated function key)
- Speakerphone mode(via dedicated function key)
- Hold (via dedicated function key)

Technical specification

Environmental conditions

- Operating ambient temperature:
  - 5 °C - +45 °C
- Humidity (non-condensing):
  - 5 % - 95 %

Package contents

- Hardware
  - Telephone base
  - Cordless DECT handset
  - Battery
  - Power adapter
  - Footstand
  - Wall mount kit
- Documentation
  - Quick Installation Guide

Snom accessories and compatible devices

- DECT handset &charging cradle
  - Up to 3 × HD3 (PN 00007011)
- Battery PN 00004627
- Power adapter: HD351A PSU
  - EU: PN 00007036
  - UK: PN 00007037
  - AU: PN 00007038

Series overview



HM201 HM2 HD100 HD101 HD1 HD300[2] HD30L[2] HD350W[2] HD351W[2] HD3

[1] Available separately
[2] Also available as analogue model
[3] DECT devices manufactured for the USA and Canada are marketed as DECT 6.0